



THE WITTERN GROUP

January 5, 2009

GENEVA – Converting the Tea Station to a Whipped Station

Parts required:

Qty	Part Number	Description	Qty	Part Number	Description
1	1217354.001	Whipper Motor Assembly Beige	1	4214369	Ingredient Canister – 22mm auger with agitator wheel (Suitable for single mix products e.g. Chai Tea)
1	4214445	Impellor Disc - Gray	1	4217745	Harness - Whipper Motor
1	4214449	Shaft Seal - Red			

Tools/materials required:

No. 2 Philips Screwdriver

Long Nose Pliers

Label maker with black Tape (to modify title of drink on menu)

Procedure:

IMPORTANT:

- Before starting the conversion ensure that machine is isolated from the electrical supply, **remove the power cord from the outlet.**
- Read through all the steps before proceeding

- Remove all Ingredient canisters
- Remove the 2 rear cover panels
- Remove the front section stainless steel shelf
- Remove the main shelf by removing the 7 securing screws shown in Fig.1; be careful to remove the 2 x black air tubes from the underside
- Remove the beige mixing chamber
- Remove the #8 screw retaining the beige mixing base and twist to remove
- Install the new 4217745 2-wire harness, 'piggy-back' with the wires connected to the 'Tea' water valve (E) as shown in Fig.1
- Connect the other end of the harness to the 1217354.001 Whipper Motor such that the + terminal of the whipper motor connects with the Red/White wire'
- Install the whipper motor assembly and secure with the #screw removed earlier
- Fit the 4214449 Red Shaft Seal onto the whipper shaft and push back to sealing face
- Fit the 4214445 Gray Impellor Disc by aligning the 'flat' on the shaft with the 'flat' inside the disc.
- Re-assemble the remaining parts remembering to refit the 2 x Black Air extraction tubes
- Exchange the Tea canister for the new 4214369 'Single Mix' type canister
- Modify the title on the menu panel to suit (i.e. only use selection codes 31 & 32) Adjust ingredient throws to suit.

